ELSEVIER

Information Processing Letters 49 (1994) 329–330

Information Processing Letters

Author Index Volume 49 (1994)

(The issue number is given in front of the page numbers.)

Ae, T., *see* **Kakugawa, H.** (4) 213–218
Amir, A., M. Farach and **S. Muthukrishnan**, Alphabet dependence in parameterized matching (3) 111–115

Belbaraka, M. and **I. Stojmenović**, On generating B-trees with constant average delay and in lexicographic order (1) 27– 32
Błażewicz, J., P. Dell'Olmo, M. Drozdowski and **M.G. Speranza**, Scheduling multiprocessor tasks on three dedicated processors (*Corrigendum*) (5) 269–270
Bonet, M.L. and **S.R. Buss**, Size-depth tradeoffs for Boolean formulae (3) 151–155
Borchers, A. and **P. Gupta**, Extending the quadrangle inequality to speed-up dynamic programming (6) 287–290
Breslauer, D., Testing string superprimitivity in parallel (5) 235–241
Buss, S.R., *see* **Bonet, M.L.** (3) 151–155

Calvert, K., Eliminating disjunctions of leads-to properties (4) 189–194
Chang, S.W., *see* **Li, T.F.** (3) 129–133
Cheng, E. and **W.H. Cunningham**, A faster algorithm for computing the strength of a network (4) 209–212
Chepoi, V. and **F. Dragan**, Computing a median point of a simple rectilinear polygon (6) 281–285
Choe, K.-M., *see* **Jung, M.-S.** (2) 63– 71
Collin, Z. and **S. Dolev**, Self-stabilizing depth-first search (6) 297–301
Cunningham, W.H., *see* **Cheng, E.** (4) 209–212

Dell'Olmo, P., *see* **Błażewicz, J.** (5) 269–270
de Luca, A. and **L. Mione**, On bispecial factors of the Thue–Morse word (4) 179–183
de Vrijer, R., *see* **Klop, J.W.** (2) 101–109
Dhall, S.K., *see* **Rhee, C.** (1) 45– 50
Dhall, S.K., *see* **Yang, S.B.** (3) 157–163
Dolev, S., *see* **Collin, Z.** (6) 297–301
Dragan, F., *see* **Chepoi, V.** (6) 281–285
Drozdowski, M., *see* **Błażewicz, J.** (5) 269–270

Farach, M., *see* **Amir, A.** (3) 111–115
Fujita, S., *see* **Kakugawa, H.** (4) 213–218

Gemmell, P. and **M. Harchol**, Tight bounds on expected time to add correctly and add mostly correctly (2) 77– 83
Gianuzzi, V., Distributed termination detection in reducible communication graphs (1) 1– 8
Goldmann, M., P. Grape and **J. Håstad**, On average time hierarchies (1) 15– 20
Grape, P., *see* **Goldmann, M.** (1) 15– 20
Gupta, P., *see* **Borchers, A.** (6) 287–290

Han, T., *see* **Jung, M.-S.** (2) 63– 71
Harchol, M., *see* **Gemmell, P.** (2) 77– 83
Håstad, J., *see* **Goldmann, M.** (1) 15– 20
Huang, C.-H., *see* **Huang, N.-F.** (4) 171–177
Huang, N.-F., C.-H. Huang and **Y.-L. Wang**, A sweepline algorithm to solve the two-center problem (4) 171–177
Huang, S.-T., *see* **Wuu, L.-C.** (5) 257–262

Jiang, T., *see* **Zhang, K.** (5) 249–254
Jovanović, Z. and **J. Mišić**, Fault tolerance of the star graph interconnection network (3) 145–150
Jung, M.-S., K.-M. Choe and **T. Han**, An efficient computation of right context for LR-based error repair (2) 63– 71

Kakugawa, H., S. Fujita, M. Yamashita and **T. Ae**, A distributed k-mutual exclusion algorithm using k-coterie (4) 213–218
Kanchanasut, K., A shortest-path algorithm for Manhattan graphs (1) 21– 25
Kann, V., Maximum bounded H-matching is MAX SNP-complete (6) 309–318
Kaplan, H. and **R. Shamir**, The domatic number problem on some perfect graph families (1) 51– 56
Khardon, R., On using the Fourier transform to learn Disjoint DNF (5) 219–222
Kim, D. and **J. Park**, Two-way dominant sequence clustering for processor scheduling (4) 203–208

Elsevier Science Publishers B.V.

Kim, S.K., The range co-minima problem (3) 117–121
Klop, J.W., A. Middeldorp, Y. Toyama and **R. de Vrijer**, Modularity of confluence: A simplified proof (2) 101–109
Kolountzakis, M.N., Selection of a large sum-free subset in polynomial time (5) 255–256

Ladermann, M. and **H. Petersen**, Notes on looping deterministic two-way pushdown automata (3) 123–127
Lakshmivarahan, S., *see* **Rhee, C.** (1) 45– 50
Lakshmivarahan, S., *see* **Yang, S.B.** (3) 157–163
Leiss, E.L., *see* **Reddy, H.N.** (6) 319–325
Leuchner, J.H., L. Miller and **G. Slutzki**, A note on the equivalence of a set of egds to a set of FDs (4) 185–188
Li, T.F. and **S.W. Chang**, An algorithm to estimate the fraction defective and the exponential mean life using unlabeled samples (3) 129–133
Liang, Y.D., *see* **Rhee, C.** (1) 45– 50
Libkin, L. and **L. Wong**, Conservativity of nested relational calculi with internal generic functions (6) 273–280

Mairson, H.G., Generating words in a context-free language uniformly at random (2) 95– 99
Middeldorp, A., *see* **Klop, J.W.** (2) 101–109
Miller, L., *see* **Leuchner, J.H.** (4) 185–188
Mione, L., *see* **de Luca, A.** (4) 179–183
Mišić, J., *see* **Jovanović, Z.** (3) 145–150
Mohanty, S.P., *see* **Panda, B.S.** (3) 139–143
Muthukrishnan, S., *see* **Amir, A.** (3) 111–115

Neiger, G., Distributed Consensus revisited (4) 195–201
Nuutila, E. and **E. Soisalon-Soininen**, On finding the strongly connected components in a directed graph (1) 9– 14

Osawa, S., *see* **Shibata, Y.** (3) 135–138

Panda, B.S. and **S.P. Mohanty**, Recognition algorithm for intersection graphs of edge disjoint paths in a tree (3) 139–143
Park, J., *see* **Kim, D.** (4) 203–208
Paul, W.J., A note on bitonic sorting (5) 223–225
Pemmaraju, S.V. and **C.A. Shaffer**, Analysis of the worst case space complexity of a PR quadtree (5) 263–267
Petersen, H., *see* **Ladermann, M.** (3) 123–127
Prodinger, H., An asymptotic comment on a paper by Analyti and Pramanik (6) 327–328

Rajsbaum, S., Upper and lower bounds for stochastic marked graphs (6) 291–295
Reddy, H.N. and **E.L. Leiss**, An O(log N) algorithm to solve linear recurrences on hypercubes (6) 319–325
Rhee, C., Y.D. Liang, S.K. Dhall and **S. Lakshmivarahan**, Efficient algorithms for finding depth-first and breadth-first search trees in permutation graphs (1) 45– 50

Sajith, G. and **S. Saxena**, Optimal parallel algorithms for coloring bounded degree graphs and finding maximal independent sets in rooted trees (6) 303–308
Saxena, S., Two-coloring linked lists is NC^1-complete for logarithmic space (2) 73– 76
Saxena, S., *see* **Sajith, G.** (6) 303–308
Shaffer, C.A., *see* **Pemmaraju, S.V.** (5) 263–267
Shamir, R., *see* **Kaplan, H.** (1) 51– 56
Shibata, Y., M. Shirahata and **S. Osawa**, Counting closed walks in generalized de Bruijn graphs (3) 135–138
Shirahata, M., *see* **Shibata, Y.** (3) 135–138
Singh, G., Real-time leader election (2) 57– 61
Slutzki, G., *see* **Leuchner, J.H.** (4) 185–188
Soisalon-Soininen, E., *see* **Nuutila, E.** (1) 9– 14
Speranza, M.G., *see* **Błażewicz, J.** (5) 269–270
Steinbach, J., Generating polynomial orderings (2) 85– 93
Stojmenović, I., *see* **Belbaraka, M.** (1) 27– 32

Tel, G., Maximal matching stabilizes in quadratic time (6) 271–272
Tel, G., *see* **van Wezel, M.C.** (5) 227–233
Ting, H.F. and **A.C. Yao**, A randomized algorithm for finding maximum with $O((\log n)^2)$ polynomial tests (1) 39– 43
Tiwari, P. and **M. Tompa**, A direct version of Shamir and Snir's lower bounds on monotone circuit depth (5) 243–248
Tompa, M., *see* **Tiwari, P.** (5) 243–248
Toyama, Y., *see* **Klop, J.W.** (2) 101–109

van Wezel, M.C. and **G. Tel**, An assertional proof of Rana's algorithm (5) 227–233
Veljan, D., Computing values of a polynomial with only few multiplications (1) 33– 37

Wang, C.-M., A new routing algorithm for cyclic shifts on BRGC hypercubes (4) 165–169
Wang, Y.-L., *see* **Huang, N.-F.** (4) 171–177
Wong, L., *see* **Libkin, L.** (6) 273–280
Wuu, L.-C. and **S.-T. Huang**, Identity assignment in uniform synchronous rings (5) 257–262

Yamashita, M., *see* **Kakugawa, H.** (4) 213–218
Yang, S.B., S.K. Dhall and **S. Lakshmivarahan**, A processor efficient MIS algorithm on random graphs (3) 157–163
Yao, A.C., *see* **Ting, H.F.** (1) 39– 43

Zhang, K. and **T. Jiang**, Some MAX SNP-hard results concerning unordered labeled trees (5) 249–254